



- *Audio prompt diagnosis on failures
- *Intelligent control and display technology.
- *comfortable airflow
- *Adopting energy saving design~photo thermal
- *High EER
- *Environment friendly

Hybrid Window Type

Model		TKC-26S	TKC-35S	TKC-52S	TKC-72S
BTU		9000 BTU	12000BTU	18000BTU	24000 BTU
Power Supply		1-220V/50Hz/60Hz	1-220V/50Hz/60Hz	1-220V/50Hz/60Hz	1-220V/50Hz/60Hz
Refrigerant		R22/R410A	R22/R410A	R22/R410A	R22/R410A
Capacity		2500W/9000BTU	3500W/12000BTU	5200W/18000BTU	7200W/24000BTU
Input Power	Cooling	600W	800W	1100W	1600W
	Heating	570W	750W	1050W	1500W
Currency (Amp)	Cooling	2.5A	3.6A	4.8A	7.3A
	Heating	2.4A	3.4A	4.6A	7.2A
Air flow (m3/hour)		390	450	520	700
Noise(dBA)		52-55	54-58	56-60	58-62
Weight (Net/Gross)		31kg/33kg	42kg/44kg	45kg/47kg	52kg/55kg
Product Dimension		450*1000*350mm	560*1100*400mm	560*1100*400mm	670*1100*455mm
Package Dimension		550*1080*440mm	620*1180*445mm	620*1180*445mm	730*1180*500mm
Quantity(20ft/40HQ)/pcs		110/265	90/230	90/230	70/160

